



A comfortable ergonomic viewing position for computer monitors is essential for preventing eye and neck strain. LiftTEC Arms move smoothly and stay in place with one-handed operation, providing easy adjustments for a perfect personal fit.

angle. Slide the mounts along the cross bar to accommodate different monitor sizes. The Arm I has a range of 21.53" and can be rotated up to 360° on the table mounts for shared viewing; 180° on the TSS column.

The LiftTEC Arm I Dual supports two monitors weighing up to 15 lbs each, either side-by-side or above one another. Supported by a LiftTEC Arm I, the Dual uses Gas Spring technology for easy positioning. Equipped with Quick Release monitor mounts, the monitors simply click in place and can be tilted to the perfect viewing

The Arm I Dual is available for mounting on a TSS column or with 3 in 1 surface mounting options. Cable clips are included to maintain a neat, organized appearance.

LiftTEC arms have a clean, modern style to suit any work environment.

Item Number	Base Option	Capacity	Range
930+1279+000	System Clamp / Grommet / Drilling Screw	2x 15 lbs	16.34"
980+1279+000	TSS Column Mount	2x 15lbs	17.6"

FEATURES

- Adjustability: tilt/turn angle, height
- Range: 16.34"
- Carrying capacity: 2 monitors weighing up to 15 lbs each
- Maximum height of monitor mount from desk surface: 11"
- Pivot: 180 degrees
- 3-in-1 table top mount options – Drilling Screw, Grommet, System Clamp 1
- Gas Spring Technology for two-fingered positioning
- Die cast aluminum construction for superior strength
- German engineered for quality
- Mounting standard: VESA 75/100

HIGHLIGHTS

--	--	--	--	--	--

BASE OPTIONS

System Clamp	Drilling Screw	Grommet	TSS Column